

## List of Compatible Device Models

### Logo Transfer Software

- As of June 2019 -

In using this software, bear in mind that the items whose settings must be selected for the projectors and the functions that can be used may differ from one projector model to another. While referring to the table below, check out that projector models are compatible with the software before using them.

#### List of models

PT-D10000	10	PT-DX610	8
PT-D12000	7	PT-DX800	8
PT-D4000	11	PT-DX810	8
PT-D5000	8	PT-DX820	4
PT-D5700	11	PT-DZ10K	4
PT-D6000	8	PT-DZ110XE	8
PT-DS100XE	8	PT-DZ12000	7
PT-DS12K	4	PT-DZ13K	4
PT-DS20K	4	PT-DZ16K	4
PT-DS20K2	4	PT-DZ16K2	4
PT-DS8500	8	PT-DZ21K	4
PT-DW100	7	PT-DZ21K2	4
PT-DW10000	10	PT-DZ570	9
PT-DW105XEA	8	PT-DZ6700	8
PT-DW11K	4	PT-DZ6710	8
PT-DW17K	4	PT-DZ680	8
PT-DW17K2	4	PT-DZ770	8
PT-DW5100	11	PT-DZ780	4
PT-DW530	9	PT-DZ870	4
PT-DW6300	8	PT-DZ8700	8
PT-DW640	8	PT-EW530	14
PT-DW730	8	PT-EW540	12
PT-DW740	8	PT-EW550	13
PT-DW750	4	PT-EW551	13
PT-DW830	4	PT-EW630	14
PT-DW8300	8	PT-EW640	12
PT-DW90XE	8	PT-EW650	13
PT-DX100	4	PT-EW651	13
PT-DX500	9	PT-EW730	12

(continued)

The software is not compatible with any device models that are not listed in "List of models".

## List of models

(continued)

PT-EX12K . . . . .	15	PT-RS20K . . . . .	4
PT-EX16K . . . . .	15	PT-RS30K . . . . .	4
PT-EX500 . . . . .	14	PT-RW330 . . . . .	6
PT-EX510 . . . . .	12	PT-RW430 . . . . .	6
PT-EX520 . . . . .	13	PT-RW620 . . . . .	4
PT-EX521 . . . . .	13	PT-RW630 . . . . .	4
PT-EX600 . . . . .	14	PT-RW730 . . . . .	4
PT-EX610 . . . . .	12	PT-RW930 . . . . .	4
PT-EX620 . . . . .	13	PT-RX110 . . . . .	4
PT-EX621 . . . . .	13	PT-RZ120 . . . . .	4
PT-EX800 . . . . .	12	PT-RZ12K . . . . .	4
PT-EZ57 . . . . .	13	PT-RZ21K . . . . .	4
PT-EZ570 . . . . .	14	PT-RZ31K . . . . .	4
PT-EZ580 . . . . .	12	PT-RZ370 . . . . .	6
PT-EZ590 . . . . .	13	PT-RZ470 . . . . .	6
PT-EZ591 . . . . .	13	PT-RZ475 . . . . .	6
PT-EZ770 . . . . .	12	PT-RZ570 . . . . .	4
PT-FW430 . . . . .	21	PT-RZ575 . . . . .	4
PT-FW530 . . . . .	13	PT-RZ660 . . . . .	4
PT-FX400 . . . . .	21	PT-RZ670 . . . . .	4
PT-FX500 . . . . .	13	PT-RZ770 . . . . .	4
PT-FZ570 . . . . .	13	PT-RZ870 . . . . .	4
PT-LB1 . . . . .	25	PT-RZ970 . . . . .	4
PT-LB1V . . . . .	25	PT-ST10 . . . . .	25
PT-LB2 . . . . .	25	PT-SW280A . . . . .	22
PT-LB2V . . . . .	25	PT-SX300A . . . . .	22
PT-LB3 . . . . .	25	PT-SX320A . . . . .	22
PT-LB75V . . . . .	26	PT-TW230 . . . . .	24
PT-LB78V . . . . .	26	PT-TW231R . . . . .	24
PT-LB90 . . . . .	26	PT-VMW50 . . . . .	13
PT-LB90NT . . . . .	25	PT-VMW60 . . . . .	13
PT-LW25H . . . . .	24	PT-VMZ40 . . . . .	13
PT-LX22 . . . . .	24	PT-VMZ50 . . . . .	13
PT-LX26 . . . . .	24	PT-VMZ60 . . . . .	13
PT-LX26H . . . . .	24	PT-VW330 . . . . .	20
PT-LX30H . . . . .	24	PT-VW340 . . . . .	17
PT-LZ370 . . . . .	23	PT-VW345N . . . . .	17
PT-MW530 . . . . .	4	PT-VW350 . . . . .	17
PT-MW630 . . . . .	4	PT-VW355N . . . . .	17
PT-MW730 . . . . .	4	PT-VW360 . . . . .	17
PT-MZ570 . . . . .	4	PT-VW430 . . . . .	18
PT-MZ670 . . . . .	4	PT-VW431D . . . . .	19
PT-MZ770 . . . . .	4	PT-VW435N . . . . .	18
PT-RQ13K . . . . .	4	PT-VW440 . . . . .	18
PT-RQ22K . . . . .	4	PT-VW530 . . . . .	17
PT-RQ32K . . . . .	4	PT-VW535N . . . . .	17
PT-RS11K . . . . .	4	PT-VW540 . . . . .	16

(continued)

The software is not compatible with any device models that are not listed in "List of models".

## List of models

(continued)

PT-VW545N	16
PT-VX400	20
PT-VX400NT	20
PT-VX405	18
PT-VX406	17
PT-VX41	20
PT-VX410	17
PT-VX415N	17
PT-VX42	17
PT-VX420	17
PT-VX421	17
PT-VX425N	17
PT-VX430	17
PT-VX45	18
PT-VX46	17
PT-VX50	17
PT-VX500	18
PT-VX501	18
PT-VX505N	18
PT-VX51	16
PT-VX510	18
PT-VX60	17
PT-VX600	17
PT-VX605N	17
PT-VX61	16
PT-VX610	16
PT-VX615N	16
PT-VZ470	17
PT-VZ570	17
PT-VZ575N	17
PT-VZ580	16
PT-VZ585N	16
TH-D10000	10
TH-DW10000	10

The software is not compatible with any device models that are not listed in "List of models".

- PT-RQ32K / PT-RZ31K / PT-RS30K
- PT-RQ13K
- PT-RQ22K / PT-RZ21K / PT-RS20K
- PT-RZ12K / PT-RS11K
- PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620
- PT-RZ670 / PT-RW630
- PT-RZ575 / PT-RZ570
- PT-DZ21K2 / PT-DS20K2 / PT-DW17K2 / PT-DZ16K2
- PT-DZ21K / PT-DS20K / PT-DW17K / PT-DZ16K
- PT-DZ13K / PT-DS12K / PT-DW11K / PT-DZ10K
- PT-DZ870 / PT-DW830 / PT-DX100
- PT-DZ780 / PT-DW750 / PT-DX820
- PT-MZ770 / PT-MW730 / PT-MZ670 / PT-MW630 / PT-MZ570 / PT-MW530

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: A/D/E/J/T/U/(blank), lens: L/(blank), cabinet color: B/K/W/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

**[Logo Data]**

○: Possible    ×: Not possible    —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

**PT-RZ475**  
**PT-RZ470 / PT-RW430**  
**PT-RZ370 / PT-RW330**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank), cabinet color: K/W/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	×	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

## ■ PT-DZ12000 / PT-D12000 / PT-DW100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	○	
	Standby	○	Transfer operations using a LAN connection cannot be performed if network standby is OFF.
	During cooling	○	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	○	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-DZ8700 / PT-DS8500 / PT-DW8300 / PT-DZ110XE / PT-DS100XE / PT-DW90XE / PT-DW105XEA

■ PT-DZ770 / PT-DW740 / PT-DX810

■ PT-DZ680 / PT-DW640 / PT-DX610

■ PT-DZ6710 / PT-DZ6700 / PT-DW6300 / PT-D6000 / PT-D5000

■ PT-DW730 / PT-DX800

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank), cabinet color: S/K/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.



## PT-DZ570 / PT-DW530 / PT-DX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

## TH-DW10000 / TH-D10000 / PT-DW10000 / PT-D10000

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/U)

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	○
	Standby	○
	During cooling	○
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	○

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	2	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

## PT-D5700 / PT-D4000 / PT-DW5100

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/U/(blank), lens: L/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 640 X 200	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

■ PT-EZ770 / PT-EW730 / PT-EX800

■ PT-EZ580 / PT-EW640 / PT-EX610 / PT-EW540 / PT-EX510

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: D/J/Z/T/(blank), lens: L/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200, 38400	
	Parity	NONE, ODD, EVEN	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.

**PT-EZ590 / PT-EW650 / PT-EW550 / PT-EX620 / PT-EX520 / PT-EZ57**  
**PT-EZ591 / PT-EW651 / PT-EW551 / PT-EX621 / PT-EX521**  
**PT-FZ570 / PT-FW530 / PT-FX500**  
**PT-VMZ60 / PT-VMZ50 / PT-VMZ40 / PT-VMW60 / PT-VMW50**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: A/D/J/K/T/(blank), lens: L/(blank), cabinet color: B/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600, 19200, 38400
	Parity	NONE, ODD, EVEN
	Projector ID	ALL, 1 to 64
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-EZ590, PT-EW650, PT-EW550, PT-EZ57, PT-EZ591, PT-EW651, PT-EW551, PT-FZ570, PT-FW530, PT-VMZ60, PT-VMZ50, PT-VMZ40, PT-VMW60 and PT-VMW50.

## PT-EZ570 / PT-EW630 / PT-EX600 / PT-EW530 / PT-EX500

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal, Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-EZ570, PT-EW630 and PT-EW530.

**PT-EX16K**  
**PT-EX12K**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	ALL, 1 to 64	
Power state	Power on	×	
	Standby	○	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-VZ585N / PT-VW545N / PT-VX615N

■ PT-VZ580 / PT-VW540 / PT-VX610 / PT-VX61 / PT-VX51

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: D/J/K/K1/T/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	Up to 1024 X 768	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	○	A magnification ratio of x1, x2, x4, and x8 can be specified for the height and width independently. However, a magnification ratio that exceeds the panel resolution cannot be specified.
Display position	Display at any position	○	Selectable up to a position in which the image does not extend out of the display area.



- PT-VZ575N / PT-VW535N / PT-VX605N
- PT-VZ570 / PT-VW530 / PT-VX600 / PT-VX406 / PT-VX46 / PT-VX60 / PT-VX50
- PT-VZ470
- PT-VW360 / PT-VX430
- PT-VW355N / PT-VX425N
- PT-VW350 / PT-VX420 / PT-VX421
- PT-VW345N / PT-VX415N
- PT-VW340 / PT-VX410 / PT-VX42

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: D/EA/J/T/Z/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-VZ575N, PT-VW535N, PT-VZ570, PT-VW530, PT-VZ470, PT-VW360, PT-VW355N, PT-VW350, PT-VW345N and PT-VW340.

■ PT-VW440 / PT-VX510

■ PT-VW435N / PT-VX505N / PT-VW430 / PT-VX501 / PT-VX500 / PT-VX405 / PT-VX45

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/EP/KEA/U/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-VW440, PT-VW435N and PT-VW430.

## PT-VW431D

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Network)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

**PT-VW330 / PT-VX400NT / PT-VX400**  
**PT-VX41**

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/EP/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-VW330.

## PT-FW430 / PT-FX400

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

# PT-SW280A / PT-SX320A / PT-SX300A

## [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	ALL, 1 to 6	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

## [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-SW280A.

## PT-LZ370

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	○
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	ALL, 1 to 6
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	191 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	○	
Screen effect	Transparent color specification	○	Set the color of the pixel in the top-left corner to a transparent color.
	Background color specification	○	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

■ PT-LW25H / PT-LX30H / PT-LX26H / PT-LX26 / PT-LX22  
 ■ PT-TW231R / PT-TW230

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

**[Communication and Transfer]**

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark	
Method of connecting to projector	LAN connection	×	
	Serial connection	○	
	Communication rate (bps)	9600, 19200	Operate at 9600 when the AMX D.D. is On. Operate at 19200 when the AMX D.D. is Off.
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Network)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

**[Logo Data]**

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	○	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	○*1	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

\*1: Background color can be set only for the PT-LW25H, PT-TW231R and PT-TW230.



## PT-LB90NT

## PT-LB3 / PT-LB2V / PT-LB2 / PT-LB1V / PT-LB1 / PT-ST10

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method			Remark
Method of connecting to projector	LAN connection	○	
	Serial connection	○	
	Communication rate (bps)	9600 *1	
	Parity	NONE *1	
	Projector ID	— *1	
Power state	Power on	×	
	Standby	○ (Standby mode: Normal)	
	During cooling	×	
	During power on process	×	
Security password setting	On and standby state	×	
	On and during display of password input screen immediately after power on	×	
	On and following password input immediately after power on	×	

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	

## PT-LB90 / PT-LB78V / PT-LB75V

Alphabet letters are omitted from the end of the above product numbers because the specifications are common regardless of whether the alphabet letters are included.

\* Alphabet letters at end (place of destination: E/EA/U/(blank))

### [Communication and Transfer]

○: Possible ×: Not possible —: Without function

Condition / State / Method		Remark
Method of connecting to projector	LAN connection	×
	Serial connection	○
	Communication rate (bps)	9600 *1
	Parity	NONE *1
	Projector ID	— *1
Power state	Power on	×
	Standby	○ (Standby mode: Normal)
	During cooling	×
	During power on process	×
Security password setting	On and standby state	×
	On and during display of password input screen immediately after power on	×
	On and following password input immediately after power on	×

For all of the conditions, if even one of the states corresponding to each condition is “×”, sending and receiving is not possible for the projector.

\*1: The setting values cannot be changed.

### [Logo Data]

○: Possible ×: Not possible —: Without function

Item	Function	Restrictions/Compatibility	Remark
Logo	Size (width X height)	1024 X 768 dots only	
	Number of colors	192 colors	If the number of colors exceeds this value when a new logo is created (a bitmap logo is loaded), the colors are reduced in the software so that the number of colors is no more than this value.
	Number of logos that can be specified as user logos	1	
	File format	Bitmap format	
Application	Startup	○	
	No signal	—	
	Security screen	—	
Screen effect	Transparent color specification	×	
	Background color specification	×	
Enlarge	Display enlargement function on projector side	×	
Display position	Display at any position	×	