

Features

		LFE8				Video Wall					Touch Screen				
		TH-32EF1	TH-55LFE8	TH-48LFE8	TH-43LFE8	VF	LFV				BF		BQE/BFE		
						TH-55VF1H	TH-55LFFV70	TH-55LFFV6	TH-55LFFV9	TH-55LFFV8	TH-49LFFV8	TH-80BF1	TH-65BF1	TH-75BQE1	TH-65BFE1
Screen Size (inches)	32	55	48	43	55	55	55	55	55	49	80	65	75	65	
Specifications	LinkRay Compatible	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Touch Operation	-	-	-	-	-	-	-	-	-	-	●	●	●	●
	IP Rating	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Operating Time	16	16	16	16	24	24	24	24	24	24	18	18	16	16
	DIGITAL LINK	-	-	-	-	●	●	-	-	-	-	-	●	●	-
	Wireless Function	-	-	-	-	-	-	-	-	-	-	●	●	-	-
	Protective Glass	-	-	-	-	-	-	-	-	-	-	●	●	●	●
	Function Slot	-	-	-	-	-	-	-	-	-	-	SLOT 2.0		-	-
Installation	Portrait	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Multi Screen (Multi Display Setting) ³	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Daisy Chain Connection	-	-	● (IR only)		●	●	●	●	●	●	-	-	-	-
	Pre Calibration	-	-	-	-	●	●	●	●	●	●	-	-	-	-
Functions	Fan-less Design	●	●	●	●	●	-	-	-	-	-	-	-	●	●
	Built-in Whiteboard	-	-	-	-	-	-	-	-	-	-	-	-	●	●
	USB Media Player	● ⁴	● ⁴	● ⁴	● ⁴	●	●	●	●	●	●	-	-	-	-
	Memory Viewer	-	-	-	-	-	-	-	-	-	-	●	●	-	-
	Data Cloning	-	-	USB		USB/LAN		-	USB	●	●	-	-	-	-
	HDMI CEC	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Customized Image Setting	●	-	-	-	●	-	-	-	-	-	-	-	-	-
	USB Memory Network Setting	-	-	-	-	●	-	-	-	-	-	-	-	-	-
	Portrait Zoom Mode	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Screen Transfer	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Multi Input Display ⁵	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Input Search/No Signal Auto Switch Setting/Input Signal Search	●	●	●	●	●	-	●	●	-	-	●	●	●	●
	Failover/Failback	-	-	-	-	●	● ⁶	● ⁷	● ⁷	● ⁷	● ⁷	-	-	-	-
	1:1 Pixel Mode	●	●	●	●	●	●	●	●	-	-	●	●	-	-
	Color Management	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Color Enhancement	●	●	●	●	●	●	●	●	●	●	-	-	-	-
	Adaptive Contrast Correction	●	●	●	●	●	●	●	●	●	●	-	-	-	-
	Refine Enhancer	-	-	-	-	●	-	●	-	-	-	-	-	-	-
	Gradation Smoother	-	-	-	-	●	-	●	-	-	-	-	-	-	-
	Frame Creation	-	-	-	-	-	-	-	-	-	-	●	●	-	-
	Dynamic Backlight	-	-	-	-	● ⁸	-	-	-	-	-	●	●	-	-
	Set up Timer	●	●	●	●	●	●	●	-	-	-	●	●	●	●
	Off Timer Setting	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Power on Screen Delay	●	●	●	●	●	●	●	●	●	●	●	●	-	-
	Auto Setup	●	●	●	●	●	●	●	●	-	-	●	●	●	●
	No Activity Power Off	●	●	●	●	●	-	●	-	-	-	●	●	●	●
	PJ Link Protocol	●	●	●	●	●	●	●	●	●	●	●	●	-	-
	LAN Control (Network Control)	●	●	●	●	●	●	●	●	●	●	●	●	-	-
	Web Browser Control	●	●	●	●	●	●	●	●	●	●	●	●	-	-
	Remote ID Control (Function)	●	●	●	●	●	●	●	-	-	-	-	-	-	-
Serial ID Control (Function)	●	●	●	●	●	●	●	●	●	●	●	●	-	-	
Local Dimming	-	-	-	-	●	-	-	-	●	●	-	-	-	-	
ECO Mode/Power Management Mode	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Audio Input Select (Switching)	-	-	-	-	●	-	●	-	-	-	●	●	●	●	
Software	Multi Monitoring & Control Software Compatible	●	●	●	●	●	●	●	●	●	●	●	-	-	
	Early Warning Software Compatible ⁹	●	●	●	●	●	●	●	●	●	●	●	-	-	
	Video Wall Manager	●	-	-	-	●	●	●	●	●	●	-	-	-	
	Auto Display Adjustment Upgrade Kit (TY-VUK10)	-	-	-	-	●	●	●	●	●	●	-	-	-	
	Content Management Software	-	-	-	-	-	-	-	-	-	-	-	-	-	

*1: Long Reach Mode compatible
 *2: Please contact your sales company with regard to the portrait setting before installation.
 *3: The number of units that can be set as a group varies depending on the model. For details, see the Operation Manual of each model.
 *4: Some files cannot be played back even if they are in the supported format. Regarding restrictions, see the Operation Manual.
 *5: There are restrictions on the input signal and 4-Input Multi Display function. 3G-SDI input and 4K images are not supported by the 4-Input Multi Display function. For details, see the Operation Manual of each model.
 *6: Backup input only
 *7: The TH-55LFFV8/49LFF8 support only the Failover function. The switching time varies depending on the model and setting.
 *8: Multi Dynamic Backlight
 *9: The part number suffix may differ depending on the license type.
 Note: The specifications may vary depending on the model, even for the same function. For details, see the Operation Manual of each model.