



WX-AU202 | 2 CHANNEL DECT ANTENNA / RECEIVER

- Built-in 2-ch DECT wireless mic receiver
- Connects via a CAT5e/6 cable to the Panasonic's WX-AM800 Beamforming Ceiling Mic Array
- Adjustable range to accommodate room size & minimize interference with multiple systems (3 settings)
- Flexible mounting options (on wall or on ceiling)
- Mounting plate included

The WX-AU202 2 channel DECT Antenna / Receiver allows for the easy addition of 2 Panasonic DECT wireless microphones to a Panasonic Beamforming Ceiling Microphone Array system. This handy accessory connects directly to the WX-AM800 beamforming ceiling mic array (sold separately) via 1 CAT5e cable (maximum distance 195 feet). Easily pair up to 2 Panasonic DECT wireless microphones to the WX-AU202 antenna/receiver. Audio from the two DECT wireless microphone channels, along with the audio from the ceiling mic are transmitted back to the Dante network over a single CAT5e cable. Each antenna has a maximum range of 90 feet (27-meters) and is easily adjustable to 2 lower settings so you can easily accommodate room size and minimize interference with other Panasonic wireless microphone systems installed in adjacent rooms. Includes a bracket for easy mounting on a wall or ceiling. Panasonic's Microphone System Configuration Center Software, compatible with Microsoft® Windows 10 & 11, allows the user to set the room size, place the ceiling microphones, pair the microphones and adjust the range of coverage for the WX-AU202 antenna as well as configure a whole host of audio DSP settings such as Acoustic Echo Cancellation, Audio Input Ducking, Equalization, Digital Noise Reduction, Panasonic PTZ Camera integration, and more!

WX-AU202 | 2 CHANNEL DECT ANTENNA / RECEIVER

WX-AU202 SPECIFICATIONS

Antenna Field Selection	Three-step switching using Panasonic's Microphone Configuration Center Software
Wireless Frequency	1921.536 MHz to 1928.448 MHz
Reception	3 Diversity Reception
Audio Output Channels	2
Audio Output Rating	-20dBV (balanced)
Frequency Response	100Hz to 15kHz
Audio Output Connector	RJ45 (Panasonic Protocol to WX-AM800 Beamforming Ceiling Mic)
Operating Ambient Temp.	32° F to +104° F (0° C to +40°C)
LED Indicators	Power, PEG, MIC 1, MIC 2
Power Source	DC24 V from WX-AM800 Beamforming Ceiling Mic Array Compatible cables: CAT5e / CAT6 straight cable
Warranty (Parts & Labor)	3 years
Finish	Sail White (color approximate to Munsell N9.3)
Accessories Included	Mounting Plate
Dimensions (W x H x D)	8-11/32 x 7-1/4 x 1-1/4 inches (212mm x 184mm x 32mm)
Weight	1.06 lbs. (480 g)

